

# DRY MIX GUIDE

APPLICATION	PURPOSE	MATERIALS REQUIRED			
Fast Setting Concrete	Suitable for fence posts, pergola posts, clothesline posts and all applications requiring rapid setting of concrete	<b>100</b> x <b>BUILDERS CHOICE Fast Setting Concrete</b> 20 kg bags for each cubic metre of finished concrete			
General Purpose Concrete	Suitable for slabs, foundations, structural concrete (up to N25 class), handyman concrete and all applications requiring normal setting concrete.	<b>100</b> x <b>BUILDERS CHOICE General Purpose Concrete</b> 20 kg bags for each cubic metre of finished concrete			
Grey Cement Render	Suitable for most grey cement render applications.	<b>11</b> x <b>BUILDERS CHOICE Grey Mortar</b> 20 kg bags for each 10 square metre of wall area using a 10mm thickness coat			
Grey Mortar, Brickwork, Blockwork	Suitable for grey mortar applications (up to M3 mortar classification) and also for most grey cement render applications.	Brick Type	Brick Size (LxWxH)	Mortar Thickness (mm)	Number of <b>Grey Mortar 20kg</b> bags required per 1000 units
		Standard	276x110x76	10	11.0
		Modular	290x90x90	10	7.7
		Midland Longreach	305x90x76	10	8.5
		Midland Ultra & Austral Verticore	305x90x162	10	5.2
		Limestone Blocks	500x150x300 (on edge)	12	6.0
			500x300x150 (on flat)	12	18.8
For all other brick sizes, contact BGC Cement on (08) 9334 4555					

- NOTES:**
1. Keep water to a minimum. Add clean water, sufficient to make firm consistent mixture.
  2. Always refer to safety instructions and mixing recommendations as printed on the bags.